



New Zealand
6 Rakau Rd
PO Box 672
Wanganui 4541

T 0800 10 10 28
W www.parkwooddoors.co.nz
E sales@parkwooddoors.co.nz

Australia
PO Box 300
Mitcham 5062
South Australia

T 1800 681 586
W www.parkwooddoors.com.au
E sales@parkwooddoors.com.au

Parkwood Duramax Lite FTS Specifications

Version 1

Date 01/07/20

Range: Duramax Composite

Material(s): GRP/fibreglass, phenolic foam, LVL and composite PVC/resin

Finish: smooth skin

Door Thickness: 33-35mm

Warranty: 5 years on door

Construction

- GRP/fibreglass Skin
 - Made from sheet moulding compound
 - Smooth skin doors 1.6-2mm skin thickness
- LVL supporter
 - Each door is constructed using an internal structure supporter manufactured from LVL (Laminated Veneer Lumber)
- Stile of both sides
 - The stiles are one (1) piece of composite PVC stile and one (1) piece of LVL
- Top rail
 - The top rail is one (1) piece of composite PVC
- Bottom Rail
 - Bottom rail is one (1) piece of composite PVC
- Lock Block
 - Lock block is approximately 350mm long, 75mm wide, on 1 side as marked on door
- Glue
 - The glue used to bond the fiberglass door skins to the frames is Urethane Adhesive Resin
- Core
 - Phenolic foam

The FTS Duramax door can be trimmed 10mm in overall height and width (must be even amount off both sides).